

| Physical Features | | | |
|------------------------------------|---|--|--------|
| Touch screen type Capacitive touch | | | |
| Touch Screen | Touch condition | Finger, touch pen | |
| | Touch points | 10 points | |
| | Response time | ≤ 10m-sec | |
| | Sensor quantity | 4K | |
| | Touch accuracy | ±1mm | |
| | Supported OS | Windows, Linux, Android | |
| | Light transmittance | ≥89% | |
| | Item | Specifications | Unit |
| Panel | Panel size | 49 | inch |
| | Panel backlight | LED backlight | / |
| | Active display area | 1073.8 (H) x 604 (V) | mm |
| | Number of pixel | | |
| | Luminance of white | 1920x1080 | pixel |
| | Contrast ratio | 350 (Typ.) | nits |
| | | 3500:1 (Typ.) | / |
| | Viewing angle | 178/178 (wide) | degree |
| | Aspect ratio | 16:9 | / |
| | Response time | 6 | m-sec |
| | Life time | 60,000 | hours |
| PC | Processor | Intel® I5 integrated CPU 5th generation | |
| | RAM | 8G DDR3 | |
| | Hard disk | 128G SSD | |
| | Mother Chipset | Intel H81 chipset, Sandy Bridge | |
| | Video Chipset | Intel HD Graphics, Shared memory | |
| | Audio Chipset | Intel HD audio | |
| | OS | Optional for Windows (unactivated), Linux | |
| | I/O ports | 4xUSB 2.0, 1xRJ-45, 1x3.5mm jack plug, 1xHDMl, 1xVGA, 1xDC 12V | |
| | Tip: In consideration of public safety, our standard unit has a door&lock for all the sockets. Please contact us, if no needed. | | |
| Appearance | Colors | Silver Frame | |
| | Surface treatment | Powder coated | |
| | Shell material | aluminium frame, tempered glass face & cold-rolled sheet body | |
| | Screen position | Bothe Portrait and Landscape / Rotating | |
| | Wheels | No need | |
| | Installation | Free-standing | |
| | Loudspeaker | Yes, 8 Ohm/ 5 watt *2 pcs | |
| Other | Power input | AC 100 ~ 240V, 50/60 Hz | |
| | IP code | IP20 | |
| | Working temperature | 0 to 40° | |
| | Storage temperature | -15℃ to 50℃ | |
| | Working temperature | 20% ~ 80% | |
| | Storage temperature | 10% ~ 90% | |
| | Accessories | Wifi Antenna*1, bracket&screws *1, key*1 | |