

# FULL HEIGHT TURNSTILE STAINLESS STEEL

**TS-FH16**

2 Lane

Bi-direction



## SPECIFICATIONS

Size: 2100x1500x2310mm

Unlock time: 0.2s

Pass rate: 30 person/min

Pass width:  $\leq 550$ mm

Input: 100-240V

Motor: Voltage:24V

Environment: -25 - +70

Power consumption: 60W



## Functions

- Bi-directional passage
- Electrical controls for both directions
- Integration with any identification or access control system
- Automatic reset of barrier wings after each passage
- Push button switch override controls for emergency situations
- Cable or wireless remote control
- Indoor application
- Modular plug-in electronics provides for easy and quick repairs



# Technical Specifications



Size	2100x1500x2310mm
Material	1.5mm SUS304 Hairline 400
Pass Width	550mm
Passage direction	Single directional/Bi-directional
Pass rate	30-35 persons/minute
Operating time	0.2 seconds
Power input	AC100-240V,50/60HZ
Working voltage	24V
Working humidity	30%~95%
Working temperature	-40°C~+70°C
Working environment	Indoor/ Outdoor available
Communication interface	RS485, Dry contact
MCBF	5,000,000 Cycles
Application	Airports, Hotels, Governemnt Halls, etc

