



barriers are normally held in a locked position, thus denying access to the secured side. Upon reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its barriers swing automatically, thus allowing users passage to the secured side

Reliability

- SUS304 stainless steel case ensures long-lasting durability
- High quality electrical components Safety Features.
- All smooth finishing. No exposed screws.
- Ergonomic design makes card and fingerprint authentication fast & simple for users

Simplification

- Simplify structure and connection, easy to maintain.
- Control board with LCD screen, easy to operate.



FLAP BARRIER

MODEL : TS-H8008

ข้อมูลด้านเทคนิค

Cabinet material	SUS304 Stainless steel
Dimension (mm)	1500 * 200 *1000 mm
Motor	Power full Servo motor drive unit
Power requirements	AC 100-120V/200-240V , 50/60Hz
Working environment	Indoor
Speed of throughput	Maximum 30/minute
Lane width (mm)	650
Interface	<ul style="list-style-type: none">- Dry contact (Relay)- +12V level signal- DC12V pulse with width of more than 100ms ,driving current > 10mA
Panel Material	Acrylic / Glass
Panel Size	Width 200- 450 mm (Customize) Height 450-1900 mm (Customize)
Indicator Display	LED
Gate Width	500- 950 mm (Customize)
Emergency mode	Yes
Buzzer	Yes
Safety Sensor	3 pairs
Security level	Medium
MCBF	2 million

การติดตั้ง

