

TS-K100



Specifications

Power requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz
Power Consumptions	Max: 75W
Working humidity	5%-80%
Working environment	Indoor/Outdoor(if sheltered)
Working Temperature	-28 °C - 60 °C
Speed	Maximum 30/minute
Lane width(mm)	520
Footprint(mm*mm)	1120*700
Dimension(mm)	L=1120, W=180, H=985
Net weight(kg)	45
Life Time	1 million
Options/Accessories	Counter, Card Receiver Box, SUS316 Cabinet and Lid, Remote Control





Reliability

Alloy steel tripod hub and SUS304 stainless steel casework & tripod arms ensure long-lasting durability

Power conservation. Electro-magnetic locks remain in "standby mode" until turnstile is activated

Patented oil lubrication system reduces need for maintenance

High quality electrical components



Safety Features

Tripod-arms unlock & drop during emergencies/power loss

All smooth finish. No exposed screws or fasteners

Visual indicator for access granted (or denied)

Ergonomic design makes card and fingerprint authentication fast & simple for users.

Secure. Supports Anti-tailgating.



Built-in Reader Integration

integrated with our customers' preference for either card or fingerprint access control reader.

This greatly reduces installation time & expense.

associated access control readers are all factory-tested prior to shipping.



Dimensions

