

# CP-SOS-EM-26:Call Point Client - Emergency Call



## Emergency Call Station with Red Light

### DESCRIPTION

1. Cold Rolled Steel body, solid and temperature bearable
2. Handsfree hotline to call.
3. Heavy duty Vandal resistant one button.
4. CCTV and other third party equipment trigger available.
5. Lightning protection standard to ITU-T K21.
6. Waterproof grade about IP65 for outdoor.
7. Body with grounding connection protection.
8. Built-in loud speaker, noise canceling microphone.
9. AC 110v-220v powered or POE powered supply (optional).
10. The design is super thin and smart. Embed style and hanging style can be chosen .
11. Time out function optional
12. Stainless Steel/Cold Rolled Steel body (optional), If the qty over 100pcs can be To customer specification(optional).
13. Incoming call and outgoing call lamp indicator.
14. With camera:

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| <b>Total Pixels</b>      | 720P(1280*720)15fps / 1080P(1920*1080) 25fps      |
| <b>Min. illumination</b> | 0.1lux                                            |
| <b>Field of view</b>     | 150° horizontal<br>Opposite angles 170°           |
| <b>Lens</b>              | 2.75mm                                            |
| <b>Frame rate</b>        | 15fps, 25fps, MJPEG, H.264                        |
| <b>Streamline</b>        | Dual-stream at different frame rate and bandwidth |



## SPECIFICATION

VoIP SIP2.0 telephone                      DTMF dialing  
MTBF:100000hours                      MTTR: 2 hours  
Communication: Full duplex 2-way hands-free communication  
Call Control Signaling:VOIP SIP Info(DTMF), RFC 2833(DTMF)  
Power:Power over Ethernet, IEEE802.3af, Class 0 Local power,  
12VDC,Idle 2W, Max 10W  
Auxiliary Contacts:1 Aux Output, dry contact  
Contact Ratings. Load: Resistive load  
Rated load:0.3 A at 125 VAC; 1 A at 30 VDC  
Rated carry current:1A  
Max.switching voltage:125 VAC, 30VDC  
Max.switching current:1A  
Audio Codes:G.711, G.722, G.729  
Network:10/100 BaseTX Ethernet, RJ45 connectors, Cat5e or better  
IP Protocols:IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP  
LAN Protocols:Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access  
Control(IEEE 802.1x),STP(IEEE 802.1d), RSTP(IEEE 802.1d-2004)  
Programming: Non-volatile flash memory programming  
and configuration through Web GUI  
Management and Operation:DHCP and static IP, remote automatic software upgrade,  
centralized monitoring, status LED  
Echo cancellation code:G.167/G.168  
Environment conditions:  
Ambient temperature: -40℃ to 70℃.    Relative humidity:10%~95%  
Atmospheric pressure: 86~106Kpa    Circumstance noise:less than 60dB(A)

## CERTIFICATION



EMC: EN50121 (Railway application- Electromagnetic Compatibility)EN55022: emissions  
EN55024: immunity  
Ingress Protection: GB4208-93 IP66  
FCC  
ITU-T Recommendations K21

